

Rinnai



Builders Series

Continuous Flow
Hot Water



Designed for the Builder



Discover our range of cost effective 6-star models designed specifically for builders and projects.

6 Star Builders Series

Rinnai Continuous Flow hot water systems are the most technologically advanced hot water system available today. These units are designed to be energy efficient, by heating water as it passes through the unit, therefore reducing running costs and greenhouse gas emissions, add to this its compact size which allows it to be installed almost anywhere.

The range is available in 16L (6.1 star), 20L (6.0 star) or 26L (6.0 star) variants and supplied in a neutral Dune colour.

Features

- Quality Japanese design and manufactured in Rinnai's own high tech facility
- High quality componentry, engineered to last
- Quick connect system for water controller cables
- Puretemp™ temperature stability technology provides PCB controlled and perfectly stable outlet water temperature
- Superior 6+ star efficiency across the range of 16 – 26 litre units
- 15 years Heat Exchanger warranty*. Conditions apply
- Sleek and compact design
- Low flow shower head (WELS) compatible
- 1.5L/minute minimum operating flow rate
- 50°C models available[#]



[#]Adjustable up to 53°C. For 60°C plus installations a tempering valve in accordance with AS3500.4 is required.

*Made from premium materials and built to last, Rinnai provides a standard 3 year (10 Year Heat Exchanger) parts and labour warranty on all Builders series Continuous Flow hot water systems plus an optional 5 years extended Heat Exchanger warranty. Visit rinnai.com.au for full terms and conditions.

Specifications & Accessories

Model	B16	B20	B26
Bathrooms	1	1-2	2 +
Installation	External	External	External
Gas Energy Rating	6.1	6.0	6.0
Heating Capacity L/Min (raised at 25°C)	16	20	26
Height	531	531	531
Width	351	351	351
Depth	195	195	195
Weight	13kg	14kg	15kg
Gas Input (High)	124MJ/h	156MJ/h	199MJ/h
Cold Water Connection (mm)	15 (1/2")	20 (3/4")	20 (3/4")
Hot Water Connection (mm)	15 (1/2")	20 (3/4")	20 (3/4")
Gas Connection (mm)	20 (3/4")	20 (3/4")	20 (3/4")
Minimum Operating Flow (L/Min)	1.5	1.5	1.5
Factory Pre-set Temperature (°C)	50/60	50/60	50/60
Colour	Dune	Dune	Dune
Ignition	Direct electronic ignition with automatic flame sensing		
Gas Type	NG / LPG		
Electrical Supply	AC 240V 50 Hz (10 amp weatherproof power point)		
Water Controllers	Up to 4 Water Controllers can be installed		
Heat Exchanger Warranty	15 years*		
Parts and Labour Warranty	3 Years (5 Years if two or more Water Controllers are installed in domestic applications)		

ABS Recess Box (SBOX)

Manufactured from a tough ABS plastic, the SBOX is light weight, easy to handle, durable and easy to install.




Metal Recess Box (RBOX04L)

Designed to house and hide the pipe work but also create a smooth and clean finish to the installation.



Pipe Cover (PC11D)

Colour matched to enhance the installation by hiding unsightly pipe work and complement its existing surroundings.




Flue Diverter

Directing the flue gases sideways means your Rinnai Builders Series Continuous Flow unit may be installed into areas with restricted ventilation like balconies.



Security Bracket (SECBKT)

Secure your investment with a quick and easy to install security bracket





Rinnai Australia Pty Ltd

ABN 74 005 138 769

100 Atlantic Drive,
Keysborough, Victoria 3173

For further information visit

www.rinnai.com.au

or call 1300 555 545

TOTAL HOME COMFORT



HOT WATER



HEATING



COOLING

Rinnai