







ELECTRIC

CYLINDER WARRANTY DELIVERY^{2,3}





The Rheem COMPACT range now features Compact 47 and Compact 25 models, both with the benefit of compact design, for space-limited installations. Wherever space is short but strong hot water delivery is a necessity, trust Rheem Compact to deliver.

COMPACT 47 FEATURES

- Just 670mm high x 400mm diameter
- Dual handed for easier installation
- Storage capacity 50L
- 3.6 kW rating
- 7 Year Cylinder Warranty¹
- Recessed plug fittings

COMPACT 25 FEATURES

- Just 390mm high x 385mm diameter
- The smallest Rheem electric water heater
- Storage capacity 25L
- 2.4 kW, 2.4 kW with power cord or 3.6 kW rating
- 7 Year Cylinder Warranty¹
- Recessed plug fittings

WHY CHOOSE RHEEM?

- Backed by over 70 years of Rheem water heating experience
- Capacities to suit every application and hot water requirement
- Mains pressure water delivery for water that comes on steady, hot and strong!
- Full technical support through Rheem's National Service Network.





DESIGNED FOR EASY INSTALLATION

Rheem COMPACT is specifically designed for a fast and easy installation. Whilst suitable for indoor or outdoor installation, the compact size means it is the unit of choice when replacing water heaters underneath the kitchen bench, in cupboards, or in the laundry.

RHEEM'S INSIDE STORY IS JUST AS STRONG

A ceramic lining, bonded to the inside of the cylinder provides long life protection against the varying water conditions found across Australia, backed by a 7 year cylinder warranty¹.

The Rheem storage cylinder is made from specially formulated steel tough enough to withstand varying water and heating cycle pressures.


RHEEM COMPACT SPECIFICATIONS				
	Warranty		Model	
Rheem Single Element	7 Years1		111025	
Rheem Single Element Dual Handed	7 Years1			191045
Hot Water Delivery	Litres		21 ³	472
Storage Capacity	Litres		25	50
Dimensions	А	mm	390	670*
	В	mm	385	400
	С	mm	420	436
	D	mm	130	347
	Е	mm	116	142
	F	mm	56	60
	Н	degrees	27	26
	J	degrees	65	59
kW rating			2.4, 3.6	3.6
Approx. Weight Empty	kg		17	25
Inlet/Outlet Connections	Rp		Rp 3/4	Rp ³ / ₄
Relief Valve Settings	kPa		1400	1400
ECV Setting#	kPa		1200	1200
Max. Supply Pressure	kPa			
With Expansion Control Valve			960	960
Without Expansion Control Valve			1120	1120

Hot Water Hot Water Outlet \ Outlet Relief Valve Reliet Valve Α D Cold Water Inlet Cold Water

В Relief Valve Fittings (Valve shown for __ Left hand installation)

Rheem Compact 47 191045

Rheem Compact 25 111025



All water heaters operate on 240 volt single phase electricity supply. Plug and lead model suitable for indoor installation only.

- # ECV not supplied with water heater.
- * Including anode cap.
- Warranty: 7 Years on Cylinder, 3 Years Labour on Cylinder, 1 Year Parts & Labour warranty on all other components for Domestic (non-Commercial) installations
- ² Rated hot water delivery is 40L in accordance with AS/NZS4692.1, Actual delivery is 47L when tested to AS/NZS4692.1.
- ³ Hot water delivery is 21L when tested to AS/NZS4692.1

Conditions apply. See the Rheem warranty set out in the Owner's Guide & Installation Instructions or view at www.rheem.com.au/warranty





Rheem Australia Pty Ltd.

1 Alan Street, Rydalmere, New South Wales 2116, Australia PO Box 7508, Silverwater, New South Wales 2128, Australia.

